



Committed to the Cut.®

FRONTMOUNT™ MODELS	500V Series Air-Cooled		600 Series Air-Cooled		700 Series Air-Cooled					700 Series Liquid-Cooled					900 Series Air-Cooled		900 Series Liquid-Cooled							
Model #/Fuel Type	525V-42 Gas	526V-52 Gas	623T Gas		725KT Gas		727T EFI Gas			735BT Gas		725DT Diesel		729T Gas			940 EFI Gas		900D 1.3L Diesel		932 Gas			
Limited Warranty Highlights	Commercial: 2 yr. 800 hours/Residential: 4 yr. 800 hours		Commercial: 3 yr. Unlimited hours/Residential: 4 yr. 800 hours																					
Engine	724cc B&S CXi V-twin	810 cc Vanguard V-twin	694 cc Rehlko Command Pro V-twin		747 cc Rehlko Command Pro V-twin		747 cc Rehlko Command Pro EFI V-twin			993 cc Vanguard Big Block V-twin		898 cc Kubota MaxTorque™ 3-cyl.		962 cc Kubota MaxTorque™ 3-cyl.			993 cc Vanguard Big Block EFI V-twin with ETC		1.3L (1,262 cc) Kubota MaxTorque™ 3-cyl.		962 cc Kubota MaxTorque™ 3-cyl.			
Crankshaft	Vertical		Horizontal: Uniform cooling, air flow and internal lubrication																					
Air Filter	Integrated, cyclonic air cleaner with 5-step debris management system.	Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management.	Heavy-duty, cyclonic, remote-mounted, replaceable dual element.																					
Fuel Capacity	4.0 gal.		4.0 gal.		7.2 gal.					8.0 gal.		7.2 gal.			14.4 gal. (two 7.2-gal. tanks)		8.0 gal.		7.2 gal.					
LED Lights	Optional. Plug-in ready. Improves visibility while mowing.					Standard: Greater visibility while mowing.																		
Hydraulic Drive System with cooling fans	Design-matched, fully hydraulic Parker HTE Series with variable displacement piston-type pumps, and high-torque wheel motors for each drive wheel with in-line cooling fans.		Design-matched T-Drive™ hydrostatic drive systems with tandem 12 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.					Design-matched T6® hydrostatic drive systems with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.					Design-matched G3 hydrostatic drive system with Hydro-Gear variable displacement 21 cc piston-type pumps, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.											
Max Ground Speed	0 - 8.0 mph		0 - 8.5 mph		0 - 9.0 mph		0 - 10.0 mph																	
Seat	Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability.															Premier Suspension Seat adjusts for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slides fore and aft. Covered with CoolTemp™ Cordura® fabric.								
Suspension	Iso-Mounted seat/footrest.		Anti-Vibe Power Platform®																	Iso-Mounted seat/footrest.				
Steering Levers	ComfortReach™ adjustable dual steering levers. Dampened, return to neutral from forward or reverse. (Optional QuikAdjust Tilt™ levers)					QuikAdjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.																		
Cutting Width	42"	52"	48"	52"	52"	61"	52"	61"	72"	61"	72"	52"	61"	72"	52"	61"	72"	61"	72"	61"	72"			
PowerFold® Electric Deck Lift	All FrontMount™ decks feature the exclusive PowerFold® feature. Rotate the cutting deck to a near vertical position for easy cleaning and servicing of the underside of the deck. Also electrically changes cutting height at the touch of a switch. Provides a shorter footprint of the FrontMount™ tractor/deck unit in order to fit more on a trailer, and for compact storage.																							
Combo Deck Model #	3242	3252	3348	3452	3452	3661	3452	3661	3472	3661	3472	3452	3661	3472	3452	3661	3472	3661	3472	3661	3472			
Dedicated Rear Discharge Decks Model #	NA	NA	NA	3552*	3552	3761	3552	3761	3572	3761	3572	3552	3761	3572	3552	3761	3572	3761	3572	3761	3572			
Cutting Height Range	2.0 - 4.5 inches		1.25 - 5.0 inches																					
Deck Construction	Extra-deep 5.5" deck (4.5" on 3348) with anvil-edge front design improves grass lift. Robotically welded, high-strength U.S. steel deck with double-layered, formed spindle plane is nearly 1-inch thick in stress zones. Half-inch reinforcement on leading edge of deck. Massive 8-inch Sentry™ spindle flanges, anchored in a 6-bolt pattern spread the force of impact for greater strength and level cut. Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Quik-D-Tatch® feature allows deck to be removed to add implements. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection. 61- and 72-inch decks feature a splined-shaft drive.																							
Hydraulic Lift	NA					Optional - Lifts deck to clear curbs and trailer ramps										Standard - Lifts deck to clear curbs and trailer ramps								
Deck Wheels	9 x 3.5-4 flat-proof					11 x 4-5 flat-proof	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic			
Drive Tires Turf and bar tread tire options available	20 x 8-10 Turf		20 x 10-8 Turf*		22 x 11-10 Bar Tread															24 x 12-12 Bar Tread				
Tail Wheels 13 x 6.5-6	Single-Fork	Wide-Stance, Single-Fork	Single-Fork		Wide-Stance, Single-Fork																			

*623T, equipped with 3552 (rear discharge) deck requires 22 x 11-10 turf, 22 x 11-8 bar tread or 22 x 11-12 Tweel® drive tires.

See your dealer for specifications on specific models or visit grasshoppermower.com.

© 2025 The Grasshopper Company Form 1225-170930 Litho in U.S.A. Models may be shown with optional equipment.

FrontMount™ Accessory and Implement Chart			
	500V Series	600 Series	700/900 Series
AERA-vator™		40"	40"/60"
Dethatcher	526V-52/623T - 46"		46"/60"
Dozer Blades	48"		48"/60"
Edge-EZE™	526V-52	•	•
PowerVac™	8F/8HT	8F/8HT/12F/12HT	
PowerVac™ 15B		•	•
PowerVac™ HighLift™ 15B			•
PowerVac 25			•
Rear Discharge Decks		•*	•
Remote Vac		•	•
Side Discharge Control Kit	•	•	•
Shielded Sprayer		53"/133"	
Snowthrower	48"		48"/60"
Sunshade Canopy	Aluminum or Vinyl		
Turbine Blower			•
V-Plow			•
Winter Cab			•
Premier Suspension Seat		•	• (Std on 940)
Footrest Riser			•
Michelin® X® Tweel® 22 x 11-12 Drive Tires		•	700 Series
Michelin® X® Tweel® 24 x 12-12 Drive Tires			900 Series
Michelin® X® Tweel® 13 x 6.5-6 Deck Wheels (72")			•
Michelin® X® Tweel® 13 x 6.5-6 Tail Wheels	•	•	•

