

200V-G4 SERIES AIR-COOLED MIDMOUNT™

Take performance
to the next level.



LIMITED WARRANTY†

2 YEAR
— 800 HRS —
COMMERCIAL

LIMITED WARRANTY†

4 YEAR
— 800 HRS —
RESIDENTIAL

225V-G4

52 61

747cc, V-twin, OHV
Rehiko Confidant
gasoline engine

226V-G4

52 61

810cc, V-twin, OHV
Vanguard
gasoline engine

227VKW-G4

52 61

852cc, V-Twin, OHV
Kawasaki FX
gasoline engine

Mowing speeds up to 9 MPH and
5.00 acres/hr. based on 61" cutting width*
For more details visit:
grasshoppermower.com/acres



Enjoy comfort, performance and durability with a compact 200V Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, lets you stay comfortably in control – even at faster mowing speeds. A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

Choose from three V-twin vertical-shaft engines. The Model 225V-G4 is powered by a 747cc Rehiko engine, the Model 226V-G4 with an 810cc Vanguard engine, or the Model 227VKW-G4 with an 852cc Kawasaki engine. All models feature G4 Hydro-Gear ZT-4400 transmissions, which are self-contained, heavy-duty commercial transaxles that provide powerful, smooth response. Integrated cooling fans and 1-3/8-inch axles extend service life, and best-in-class transmission fluid change intervals reduce costs and maintenance time. Grasshopper's intelligent design transfers more power to the cutting deck to maintain optimum blade tip speed and enhance cut quality.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

MANICURED CUT

5.5-inch-deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional four-spindle 4XRD dedicated rear-discharge decks evenly distribute clippings under the mower and out back for a smooth cut and no windrowing.

COMFORT & ERGONOMICS

The deep-cushioned, deluxe Premium Comfort seat features a coil-spring suspension and padded lumbar support with sliding 2-inch fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration even before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use.

QuikAjust Tilt™ steering levers with "no tools" adjustment provide a 9-inch range for maximum comfort and fit.

The 6.5 gal/24.6L single-fill fuel tank under the seat lowers the center of gravity of the machine, providing traction and stability for an enhanced ride. Standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

● Standard deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » 4X Rear Discharge™ decks
- » Side discharge control kit
- » Foot pedal extension kit for QuikAjust™ DropPin™ height adjustment
- » TrimAide™ anti-scalp roller kit – for 52-inch decks
- » Speed-Trimming™ heavy-duty anti-scalp roller kit – for 61-inch decks
- » Air Dam kit – for dry, dusty conditions
- » LED work lights – plug-in ready
- » Yellow beacon light
- » Sunshade Canopy – vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options
- » Heavy-duty, grass-grooming striping kit
- » Wide seat conversion kit
- » Premier Suspension Seat
- » Extended levers for taller operators
- » Foldable ROPS with adjustable seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels
- » Edge-EZE™ edger
- » Filter Minder (226V-G4 and 227V-G4KW only)
- » String Trimmer Mount Kit
- » DuraFlex™ suspension forks



Optional DuraFlex™
Suspension Fork

AIR-COOLED 200V-G4 SERIES-SPECIFICATIONS

MODEL - CUTTING WIDTH	← REHLKO →		← VANGUARD →		← KAWASAKI →	
	225V G4 52	225V G4 61	226V G4 52	226V G4 61	227V G4 52	227V G4 61
ENGINE						
Type/Displacement/Cylinders						
Rehiko Confidant gasoline/45.6 cu. in. (747cc)/V-twin	•	•				
Vanguard - gasoline/49.4 cu. in. (810cc)/v-twin			•	•		
Kawasaki FX/52.0 cu. in. (852cc)/V-Twin					•	•
Lubrication System						
Pressure Lube, Filter						
Crankshaft / Cooling System						
Vertical / Air						
Fuel / Capacity						
Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)	•	•	•	•	•	•
Air Cleaner						
Heavy-duty cyclonic air filter with QuadClean™ multi-stage air filtration	•	•				
Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management			•	•		
Heavy-duty, cyclonic, remote-mounted engine dual cleaner with replaceable element					•	•
Muffler						
Ultra-quiet, single, industrial type						

DECKS - Side Discharge or Dedicated 4X Rear Discharge (4XRD)

Construction (Robotic-welded steel)

Double-layered 10-gauge plus 10-gauge formed-steel spindle plane 0.269 in. (6.83 mm) thick with 7-gauge skirts

Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck (See Page 8 for thickness diagram)

Blades (MARBAIN®, 1/4-in.)

(3) 18 in. (45.7 cm)

(3) 21 in. (53.3 cm)

Spindle Assemblies

Turned, ground and polished 2.5 cm (approx. 1 in.) outside diameter (O.D.) precision shaft; spindle head designed to eliminate fiber wrap; double bearings, non-greasable

Spindle Housing

8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern

Spindle Cones

Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion

QuikAdjust™ DropPin™ Height Adjustment

Foot-controlled height adjustment pedal with pin

Cutting Height Range

1.0 - 4.5 in. (2.5 - 11.4 cm) in 1/4-inch increments

Blade Drive

Belt drive with single Kevlar V-belt & idler arm tensioning

DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information

4th Spindle and Grass Thrower Blade

Cast iron thrower spindle housing - 5-in. (12.7 cm) - diameter with 4-bolt pattern

(1) Grass Thrower Blade

(1) 18 in. High-Low Mulching Grass Thrower Blade

STARTER & ELECTRICAL SYSTEM

Maintenance-Free Battery/Charging Capacity/Starter

12 Volt/15 amp/solenoid shift

12 Volt/16 amp/solenoid shift

12 Volt/20 amp/solenoid shift

Ignition

Breakerless

Interlock System

Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral

ULTIMATE OPERATOR STATION™

Premium Comfort Seat; adjustable fore and aft

Premier Suspension (Grammer) Seat - slides fore and aft and adjusts to operator's size and weight

Operator Protection

Rollover Protection Structure (ROPS) with seat belt

Suspension

Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™)

MODEL - CUTTING WIDTH	← REHLKO →		← VANGUARD →		← KAWASAKI →	
	225V G4 52	225V G4 61	226V G4 52	226V G4 61	227V G4 52	227V G4 61
Console-Mounted Instruments						
Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.	•	•	•	•	•	•
Work Lights (Pre-wired)						
LED (optional)						
TRANSMISSION & STEERING						
Type						
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans; integrated transaxles with 12cc piston pumps and gear reduction, internal disc brakes, and 1-3/8 inch axles	•	•	•	•	•	•
Filtration/Hydro Fluid						
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change						
Speed						
0 - 9.0 mph (0 - 14.5 kph) forward	•	•	•	•	•	•
0 - 6.0 mph (0 - 9.7 kph) reverse						
Turning Radius						
True zero degree, turns within own length with counter-rotating, independently powered drive wheels						
Steering						
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position						
Brakes						
Dynamic braking through hydrostatic transmission						
Parking Brake						
Internal disc brake in transmission						
TIRE SIZES						
Drive Wheels - Standard (5-bolt pattern)						
23 x 10.5-12 turf type, 4-ply rated	•	•	•	•	•	•
24 x 12-12 turf type, 4-ply rated	•	•	•	•	•	•
24 x 12-12 bar tread, 4-ply rated	•	•	•	•	•	•
24 x 12-12 Airless Turf Tweek Drive Wheel	•	•	•	•	•	•
Front Casters						
13 x 6.5-6 rib tread, pneumatic with double-sealed bearings						
DIMENSIONS (Mower & Deck)						
Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.) Mulching kit optional.						
53.5 in. (135.9 cm)/76.0 in. (193.0 cm)	•	•	•	•	•	•
62.5 in. (158.8 cm)/79.0 in. (200.7 cm)	•	•	•	•	•	•
Height (Seat back)						
46.0 in. (116.8 cm)						
Height (Seat cushion)						
30.0 in. (76.2 cm)						
Height (ROPS)						
68.0 in. (172.7 cm)						
Drive Tire Track Width (outside edge to outside edge)						
50.0 in. (127.0 cm)						
WEIGHT						
Uncrated: (Mower & Deck) 960 lbs. (435.4 kg)			•			
Uncrated: (Mower & Deck) 980 lbs. (444.5 kg)	•					
Uncrated: (Mower & Deck) 990 lbs. (449.1 kg)					•	
Uncrated: (Mower & Deck) 1030 lbs. (467.2 kg)				•		
Uncrated: (Mower & Deck) 1050 lbs. (476.3 kg)		•				
Uncrated: (Mower & Deck) 1060 lbs. (480.8 kg)						•
Mulching Package (Package includes high-low mulching blades.)						
29 lbs. (13.2 kg)	•		•		•	
36 lbs. (16.3 kg)		•		•		•

